



- NOTES:
- THIS DRAWING IS MEANT TO PROVIDE CUSTOMER MOUNTING DATA ONLY. ALL DIMENSIONS ARE REFERENCE UNLESS OTHERWISE SPECIFIED.
  - THE TORQUE INFORMATION CONTAINED IN THIS DOCUMENT IS FOR REFERENCE ONLY. IT IS RECOMMENDED THAT THIS BRAKE BE TESTED IN THE SPECIFIC APPLICATION TO VERIFY PERFORMANCE.
  - MAXIMUM OPERATING PRESSURE IS 3,000 PSI [207 BAR]. PRESSURE SPIKES OR SURGES NOT TO EXCEED 4,000 PSI [276 BAR].
- △ MOUNT ADAPTER PLATE TO GEAR REDUCER USING TWO 1/2-13 UNC-2A SOCKET HEAD CAP SCREWS OF SUITABLE LENGTH.
- △ ATTACH ADAPTER PLATE TO BRAKE USING TWO GRADE 8 HEX HEAD BOLTS 1/2-13 UNC-2A X 3.5" [88.9 mm] LONG.

NLL	A	30109	RELEASE FOR PRODUCTION	07-03-18	JAH
CHKR	SYM	ECO	DESCRIPTION	DATE	BY
CS DRAWING	CS 103029	DO NOT SCALE THIS DRAWING. PROPRIETARY DATA: NOT TO BE DISCLOSED, USED, OR DUPLICATED FOR PROCUREMENT OR MANUFACTURING PURPOSES, EXCEPT AS AUTHORIZED IN WRITING BY AUSCO, INC.			
CC DRAWING	CC 103029	 			
A	A	4000 [452]	210 [14.5]	Ø1.00 [25.4] KEY	Ø1.00 [25.4] KEY
MOTOR	REDUCER	RATED TORQUE (LB IN) [Nm]	RELEASE PRESSURE (PSI) [BAR]	INPUT (INTERNAL)	OUTPUT (EXTERNAL)
MOUNTING FLANGE SAE J744				SPLINE DATA	
PROJECT	DATE	PART NAME CUSTOMER CONFIGURATION			
ADR30109	07-03-18	M/D DRY BRAKE SAE "A"			
DESIGNER	SCALE	PART NUMBER			
J. HOAR	1.000	CC103029			