



B2

- THIS DRAWING IS MEANT TO PROVIDE CUSTOMER MOUNTING DATA ONLY. ALL DIMENSIONS ARE REFERENCE UNLESS OTHERWISE NOTED.
- THE TORQUE INFORMATION CONTAINED IN THIS DOCUMENT IS FOR REFERENCE ONLY. IT IS RECOMMENDED THAT THIS BRAKE BE TESTED IN THE SPECIFIC APPLICATION TO VERIFY PERFORMANCE.
- MAXIMUM OPERATING PRESSURE IS 3000 PSI [206.8 BAR]. PRESSURE SPIKES AND SURGES NOT TO EXCEED 4000 PSI [275.8 BAR].

KMc	C3	27100	ADDED DUAL UNITS	08-01-12	SSS
KMc	C2	27100	WAS 2.06[52,3]	08-01-12	SSS
KMc	C1	27100	WAS 0.65[16,5]	08-01-12	SSS
	B3	22165	WAS PROJECT 4344	01-24-05	LTC
	B2	22165	UPDATED NOTES	01-24-05	LTC
	B1	22165	REDRAWN IN PRO/E	01-24-05	LTC
HB	A	10435	RELEASED FOR PRODUCTION	08-19-97	SJS

CHKR	SYM	ECO	DESCRIPTION	DATE	BY

<small>DO NOT SCALE THIS DRAWING PROPRIETARY DATA - NOT TO BE DISCLOSED, USED, OR DUPLICATED FOR PROCUREMENT OR MANUFACTURING PURPOSES, EXCEPT AS AUTHORIZED IN WRITING BY AUSCO, INC.</small>			
PROJECT 4579	DATE 07-14-97		
DESIGNER D. J. BIRD	SCALE 1.000	PART NUMBER CC75845	

MOD A	B	3800 [429,3]	215 [14,8]	SAE 6B	SAE 6B
MOTOR	REDUCER	RATED TORQUE (LB IN) [N-m]	RELEASE PRESSURE (PSI) [BAR]	(INPUT) (INTERNAL)	(OUTPUT) (EXTERNAL)
MOUNTING FLANGE SAE J744		SPLINE DATA			